



# CCF700 Serie

Coaxial connector





... the suitable connector for cockpit equipments!

### Catalog







The CCF700 are miniature coaxial connectors for civil and military applications, used on avionic, at sea and on land based systems.

The function of this connector is to supply power to the illuminated surfaces of many items of avionic equipments

#### Climatic and mechanical characteristics

	CCF700
Operating temperature range	-30°C to + 120°C

#### Electrical characteristics


	CCF700
Nominal current	5 A
Rating current	7.5A
Dielectric strength	500VDC
Contact resistance	≤ 8 mOhms
Insulation resistance	>5000 MOhms

#### Material and plating

	Material	Plating
Connector shell	Brass	Gold
Insulator	PTFE, DAP	•
Contacts	Copper alloy	Gold

#### ◆ CCF700P


Male coaxial plug 2 contacts for PCB



Corner cut indicates center pins (positive) Weight : 0.71gr

#### ◆ CCF700S

Female coaxial receptacle 2 solder cup contacts




Wire used: Gauge 20

Weight: 5.27gr

Excentric limit of the floating part : Diam. 1 Max

#### Panel holing

For thickness 2.5, you must make a chamber




T.G +/- 0.1

CEZOO

# Catalogs

#### Ask for our other catalogs:





Find more on

BERNIER

## www.bernier.tm.fr

This catalogue and its content are BERNIER property, all rights reserved

All information contained in this catalogue can be changed without prior notice

Dimensions in mm

